



W-M1B201



Specifications

General

- Power Input Range 10~60VDC
- Power Consumption 2.2W@24VDC
- Watchdog Timer System(1.6 second Fixed)
- Connector Communication (Programmable)
1 x plug-in terminal block (#16 ~ 30 AWG)
- Temperature (Operating) -25~70°C
- Humidity 5~95%
- Temperature (Storage) -30~75°C
- Interface RS-485
- Communication Protocol Modbus/RTU
- Communication Speed Serial: From 1200 to 115.2k bps
- Communication Distance Serial: 1.2km
- Isolation Protection 3000VDC

Analog Output

- Channels 8
- Voltage Output Range $\pm 5V, \pm 10V, 0-5V, 0-10V$
- Current Output Range 4~20mA, 0~20mA
- Disconnection Detection For Current Output
- Channel Independent configuration Yes
- Output Response Time 10ms per channel
- Resolution 12-bit
- Accuracy $\pm 0.1\%FSR$
- Programmable Output Slope Voltage: 0.0625~512V/sec.
Current: 0.125~1024mA/sec.
- Voltage Output Capability 10V @ 10mA
- Current Output Capacity 500Ω
- Power On Value Yes, Programmable
- Safety Value Yes, Programmable
- LED Display Analog Output and Fault Indicators