

**OPM 17**  
17" Open Frame flat panel Monitor



**System**

- Open Frame structure with strengthened glass
- **Mounting:** Panel mount
- **Construction:** heavy duty steel chassis with VESA 75/100mm standard screw holes
- **Input signal:** VGA, AV IN ( optional )
- **Control:** on rear panel
- **Power Supply:** External 36 W DC 12 V power adapter
- **OS Support:** MS DOS, Windows 98/SE, Windows NT 4.0, Windows 2000, Windows XP
- **Dimensions:** (WxHxD): 428.6x342.6x50 mm
- **Viewing Angle:** horizontal ( +70° - -70°), ( +70° - - 70C°)
- **Signal Connector:** 15 Pin D-SUB, AV connector ( optional)
- **OSD:** Brightness, Contrast, H/V Position, Color, Phase, Clock, Management
- **Speaker:** 2 x 2 Watt internal speaker
- 

**LCD**

- **Display Type:** 17 TFT Active Matrix Panel
- **Light Luminance:** 260cd/m<sup>2</sup>
- **Max. Resolution:** 1280 x 1024
- **Max. Colors:** 262 M colors
- **Response Time:** 16 ms
- **Back-Light MTBF :** 50000 hrs
- **Pixel Pitch :** 0.264\*0.264 mm
- **Contrast Ratio:** 450: 1



**Touchscreen (optional)**

- **Type:** Analog resistive
- **Resolution:** continuous
- **Light transmission:** 79% or more
- **Controller:** RS-232 interface ( or USB optional)
- **Power consumption:** < 5V @100 Ma
- **Software Driver:** Support Windows 98/NT/2000/ME/XP
- **Lifetime:** 100 million times

**Environmental**

- **Operation temperature:** 0°C to 45 °c
- **Storage temperature:** -20°C to 60°C
- **Storage humidity:** 10% to 95%@40°C, non-condensing
- **Vibration :** 10 – 150 Hz, 0.15 mm 10cycles 1G
- **Shock:** 30 G peak acceleration ( 11 msec. duration)

[www.acceed.com/](http://www.acceed.com/) **OPM-17** [www.acceed.com/](http://www.acceed.com/) **OPM-17T**  
**17" LCD Open Frame Display**

**Ordering Information**

- **OPM-17:** 17" TFT LCD monitor, 48W DC 12 V Power Adapter
- **OPM-17 T:** 17" TFT LCD monitor, w/ Resistive Touchscreen, 48 "W DC 12 V Power Adapter

**Dimension**

