

# P114U


PCI PORT Card

## Universal PCI Four Port Card

---

**Flexible 5V power supply only PCI card**

**RS232/RS422 / RS485 selectable**



- Suitable for **Windows NT**
  - Suitable for **WIN95/98/Me**
  - Suitable for **WIN2000/XP**
  - Suitable for **WIN7/Vista**
  - Suitable for **DOS Power User**
  - Suitable for **Linux System**
  - Suitable for **UNIX Workgroup**
- 
- ◆ Support 5V & 3.3V PCI slot.
  - ◆ IRQ & I/O mapping automatically assigned by PCI plug & play function.
  - ◆ Just use 5V power supply for RS232, RS422 & RS485 serial port.
  - ◆ Each serial port can set to RS232, RS422 or RS485 independently.
  - ◆ Support Auto-Data-Direction-Control feature in RS485.

# P114U Specification

## System Structure:

- ▲ intelligent PCI PORT Card.
- ▲ external cable with four standard DB25/DB9 connector.

## Serial Communication Controller:

- ▲ type : 16550A compatible with PGA support.
- ▲ speed : 1.8432MHz.

## Software Compatibility:

- ▲ DOS Library
- ▲ WIN7/Vista32
- ▲ WIN2000/XP
- ▲ WIN95/98/Me
- ▲ Windows NT
- ▲ Linux
- ▲ SCO OpenServer

## System I/O & IRQ mapping:

- ▲ one 32byte and one 8byte I/O mapping assigned by PCI BIOS.
- ▲ one IRQ mapping assigned by PCI BIOS.

## Port capability:

- ▲ Number of port : 4 ports per card.
- ▲ Interface : RS232,RS422 or RS485 selectable independently.
- ▲ Baud Rate :  
each port can be configured to 50~115200bps.
- ▲ Connector type :  
DB25 male connector. (with A400 cable)  
DB9 male connector. (with P485 cable)

## Hardware Compatibility:

- ▲ 5V & 3.3V PCI bus slot.

## Dimension:

- ▲ P114U card: 12.0 \* 10.0 cm.

## Environment:

- ▲ operating temperature : 0°C to 55°C .
- ▲ operating humidity : 10% to 95% RH.
- ▲ storage temperature : 0°C to 65°C .
- ▲ storage humidity : 5% to 95% RH.

## ☆ Accessories:

TB485 : DB9 Female to RS485 terminal block kit.



## ☆ Other relative 5V power supply only eight port card product line:

Model	RS232	RS422	RS485
P5584U	4	0	0
P104UP	4	0	0
P134U	0	4	4
P114U	4	4	4



## RAYON TECHNOLOGY CO., LTD.

2F, No. 177, Chung Shan 2 Rd., Lu Chou city, Taipei Hsien, Taiwan.

TEL: 886-2-82858362 FAX: 886-2-82857065

E-Mail: [rayon@ms1.hinet.net](mailto:rayon@ms1.hinet.net)

WEB: <http://www.computex.com.tw/rayon>

WEB: <http://www.rayontech.com>