

cPCI-9116 Series

64-CH 16-Bit 250 kS/s Multi-Function DAQ Modules

Features

- 3U Eurocard form factor, CompactPCI compliant (PICMG 2.0 R2.1)
- 16-bit A/D resolution
- Up to 250 kS/s sampling rate
- 64-CH single-ended or 32-CH differential inputs
- On-board 1k-sample A/D FIFO
- Bipolar or unipolar analog input ranges
- Programmable gains of x1, x2, x4, x8
- 512-configuration channel-gain queue
- Bus-mastering DMA for analog inputs
- 8-CH TTL digital inputs and 8-CH TTL digital outputs
- 1-CH 16-bit general purpose timer/counter
- Rear I/O available on cPCI-9116R

Operating Systems

- Windows 2000/NT/XP/9x
- DOS
- Red Hat Linux
- Windows CE (call for availability)

Recommended Software

- VB/VC++/BCB/Delphi
- DAQBench

Driver Support

- PCIS-DASK for Windows 2000/NT/XP/9x
- PCIS-DASK/X for Red Hat Linux
- PCIS-OCX ActiveX controls
- PCIS-LVIEW/PnP for LabVIEW **NEW!**



Introduction

ADLINK cPCI-9116 series are high-density and high-resolution multifunction DAQ modules for PXI/CompactPCI form factor. The devices can sample up to 64 AI channels with different gain settings and scan sequences. It makes them ideal for dealing with high-density analog signals with various input ranges and sampling speeds. The cPCI-9116 devices feature flexible configurations on analog inputs. They provide analog inputs with 4 programmable input ranges for both bipolar and unipolar inputs. The A/D on the cPCI-9116 devices features a sampling rate of up to 250 kS/s with resolution at 16 bits. These devices also offer differential mode for 32 AI channels in order to achieve maximum noise elimination.

The cPCI-9116 series also feature 1-CH 16-bit general purpose timer/counter, 8-CH TTL digital inputs and 8-CH TTL digital outputs. The cPCI-9116R allows I/O connectivity to be routed through the backplane via J2/P2 allowing a rear I/O transition module to be inserted, which is capable of efficient trouble-shooting and maintenance. ADLINK cPCI-9116 devices deliver cost-effective and reliable data acquisition capabilities, and are ideal for a broad variety of applications.

Specifications

Analog Input

- Number of channels: 64 single-ended or 32 differential (software selectable per channel)
- Resolution: 16 bits
- Maximum sampling rate: 250 kS/s
- Input signal ranges (software programmable)

| Gain | Input Range | |
|------|-------------|-------------|
| | Bipolar | Unipolar |
| 1 | ±5 V | 0 to 10 V |
| 2 | ±2.5 V | 0 to 5 V |
| 4 | ±1.25 V | 0 to 2.5 V |
| 8 | ±0.625 V | 0 to 1.25 V |

Accuracy

| Gain | Accuracy |
|------|-----------------------|
| 1 | 0.01 % of FSR ± 1 LSB |
| 2, 4 | 0.02 % of FSR ± 1 LSB |
| 8 | 0.04 % of FSR ± 1 LSB |

- Input coupling: DC
- Overvoltage protection: Continuous ±35 V
- Input impedance: 1 GΩ
- Trigger modes: Software, pre-trigger, post-trigger, middle-trigger, delay-trigger, and repeated trigger
- Channel-gain queue size: 512 configurations
- FIFO buffer size: 1 k samples
- Data transfers: polling, interrupt, bus mastering DMA

Digital I/O

- Number of channels: 8 inputs and 8 outputs
- Compatibility: 5 V/TTL
- Data transfers: programmed I/O

General-Purpose timer/counter

- Number of channels: 1
- Resolution: 16 bits
- Compatibility: 5 V/TTL
- Base clock available: 24 MHz, external clock up to 24 MHz

General Specifications

- I/O connector: 100-pin SCSI-II female
- Operating temperature: 0 to 55 °C
- Storage temperature: -20 to 80 °C
- Relative humidity: 5 to 95%, noncondensing
- Power requirements

| +5V | +12V |
|----------------|----------------|
| 560 mA typical | 100 mA typical |

- Dimensions (not including connectors) 160 mm x 100 mm

Termination Boards

DIN-100S

Termination Board with a 100-pin SCSI-II Connector and DIN-Rail Mounting (Including One 1-meter ACL-102100 Cable)

Ordering Information

- **cPCI-9116**
64-CH 16-Bit 250 kS/s Multi-Function DAQ Module
- **cPCI-9116R**
64-CH 16-Bit 250 kS/s Multi-Function DAQ Module with Rear I/O
- **cPCI-9116/6U**
64-CH 16-Bit 250 kS/s Multi-Function DAQ Module with 6U Panel

Note: Rear I/O version can not be used in PXI chassis due to signals conflict with PXI bus

Pin Assignment

| | | | | |
|--------------|----|-----|------------|------|
| U_CMMD | 1 | 51 | AGND | |
| AI0 (AIH0) | 2 | 52 | (AIL0) | AI32 |
| AI1 (AIH1) | 3 | 53 | (AIL1) | AI33 |
| AI2 (AIH2) | 4 | 54 | (AIL2) | AI34 |
| AI3 (AIH3) | 5 | 55 | (AIL3) | AI35 |
| AI4 (AIH4) | 6 | 56 | (AIL4) | AI36 |
| AI5 (AIH5) | 7 | 57 | (AIL5) | AI37 |
| AI6 (AIH6) | 8 | 58 | (AIL6) | AI38 |
| AI7 (AIH7) | 9 | 59 | (AIL7) | AI39 |
| AI8 (AIH8) | 10 | 60 | (AIL8) | AI40 |
| AI9 (AIH9) | 11 | 61 | (AIL9) | AI41 |
| AI10 (AIH10) | 12 | 62 | (AIL10) | AI42 |
| AI11 (AIH11) | 13 | 63 | (AIL11) | AI43 |
| AI12 (AIH12) | 14 | 64 | (AIL12) | AI44 |
| AI13 (AIH13) | 15 | 65 | (AIL13) | AI45 |
| AI14 (AIH14) | 16 | 66 | (AIL14) | AI46 |
| AI15 (AIH15) | 17 | 67 | (AIL15) | AI47 |
| AI16 (AIH16) | 18 | 68 | (AIL16) | AI48 |
| AI17 (AIH17) | 19 | 69 | (AIL17) | AI49 |
| AI18 (AIH18) | 20 | 70 | (AIL18) | AI50 |
| AI19 (AIH19) | 21 | 71 | (AIL19) | AI51 |
| AI20 (AIH20) | 22 | 72 | (AIL20) | AI52 |
| AI21 (AIH21) | 23 | 73 | (AIL21) | AI53 |
| AI22 (AIH22) | 24 | 74 | (AIL22) | AI54 |
| AI23 (AIH23) | 25 | 75 | (AIL23) | AI55 |
| AI24 (AIH24) | 26 | 76 | (AIL24) | AI56 |
| AI25 (AIH25) | 27 | 77 | (AIL25) | AI57 |
| AI26 (AIH26) | 28 | 78 | (AIL26) | AI58 |
| AI27 (AIH27) | 29 | 79 | (AIL27) | AI59 |
| AI28 (AIH28) | 30 | 80 | (AIL28) | AI60 |
| AI29 (AIH29) | 31 | 81 | (AIL29) | AI61 |
| AI30 (AIH30) | 32 | 82 | (AIL30) | AI62 |
| AI31 (AIH31) | 33 | 83 | (AIL31) | AI63 |
| AGND | 34 | 84 | AGND | |
| +15Vout | 35 | 85 | -15Vout | |
| N/C | 36 | 86 | N/C | |
| DI0 | 37 | 87 | DO0 | |
| DI1 | 38 | 88 | DO1 | |
| DI2 | 39 | 89 | DO2 | |
| DI3 | 40 | 90 | DO3 | |
| DI4 | 41 | 91 | DO4 | |
| DI5 | 42 | 92 | DO5 | |
| DI6 | 43 | 93 | DO6 | |
| DI7 | 44 | 94 | DO7 | |
| ExtTimeBase | 45 | 95 | N/C | |
| ExtTrg | 46 | 96 | GP_TC_CLK | |
| SSH_OUT | 47 | 97 | GP_TC_GATE | |
| GP_TC_GATE | 48 | 98 | GP_TC_UPDN | |
| +5Vout | 49 | 99 | +5Vout | |
| DGND | 50 | 100 | DGND | |