

Output rating	Common	Interrupt	Connector	Software			Page	Name
				ACX-PAC(W32)	API-PAC(W32)	DDE SERVER(W32)		
-	16	32 interrupt signals,1 interrupt request	37-pin D-type	○	Attached	-	B-05	PI-32L(PCI)H
-	16	4 interrupt signals,1 interrupt request	37-pin D-type	○	Attached	○	B-05	PI-32L(PCI)
-	16	32 interrupt signals,1 interrupt request	96-pin Half Pitch	○	Attached	-	B-05	PI-64L(PCI)H
-	16	4 interrupt signals,1 interrupt request	96-pin Half Pitch	○	Attached	○	B-05	PI-65L(PCI)
-	16	16 interrupt signals,1 interrupt request	100-pin	○	Attached	-	B-06	PI-128L(PCI)
35VDC 100mA	16	-	37-pin D-type	○	Attached	○	B-07	PO-32L(PCI)H
35VDC 100mA	16	-	37-pin D-type	○	Attached	-	B-07	PO-32L(PCI)
35VDC 100mA	16	-	96-pin Half Pitch	○	Attached	-	B-07	PO-64L(PCI)H
35VDC 100mA	16	-	96-pin Half Pitch	○	Attached	○	B-07	PO-65L(PCI)
35VDC 100mA	16	-	100-pin	○	Attached	-	B-08	PO-128L(PCI)
35VDC 100mA	16	16 interrupt signals,1 interrupt request	37-pin D-type	○	Attached	-	B-09	PIO-16/16L(PCI)H
35VDC 100mA	16	4 interrupt signals,1 interrupt request	37-pin D-type	○	Attached	○	B-09	PIO-16/16L(PCI)
35VDC 100mA	16	32 interrupt signals,1 interrupt request	96-pin Half Pitch	○	Attached	-	B-09	PIO-32/32L(PCI)H
35VDC 100mA	16	4 interrupt signals,1 interrupt request	96-pin Half Pitch	○	Attached	○	B-09	PIO-32/32L(PCI)
35VDC 100mA	16	16 interrupt signals,1 interrupt request	100-pin	○	Attached	-	B-10	PIO-64/64L(PCI)
35VDC 50mA	16	4 interrupt signals,1 interrupt request	96-pin Half Pitch	○	Attached	○	B-10	PIO-32/32F(PCI)
-	Common for all the channels	4 interrupt signals,1 interrupt request	37-pin D-type	○	Attached	○	B-06	PI-32B(PCI)
35VDC 100mA	Common for all the channels	-	37-pin D-type	○	Attached	○	B-08	PO-32B(PCI)
35VDC 100mA	Common for all the channels	4 interrupt signals,1 interrupt request	37-pin D-type	○	Attached	○	B-10	PIO-16/16B(PCI)
35VDC 100mA	Common for all the channels	4 interrupt signals,1 interrupt request	96-pin Half Pitch	○	Attached	○	B-10	PIO-32/32B(PCI)H
5VDC 6.4mA	Common for all the channels	4 interrupt signals,1 interrupt request	37-pin D-type	○	Attached	○	B-11	PIO-16/16TB(PCI)
120VAC/VDC 100mA	16	16 interrupt signals,1 interrupt request	37-pin D-type	○	Attached	-	B-11	PIO-16/16RY(PCI)
125VAC/VDC 2mA	Independence for all the channels	-	37-pin D-type	○	Attached	○	B-11	RRY-16C(PCI)
100VAC/VDC 0.5mA	8	-	37-pin D-type	○	Attached	○	B-11	RRY-32(PCI)
30VDC 40mA	Common for all the channels	4 interrupt signals,1 interrupt request	37-pin D-type	○	Attached	○	B-12	PIO-16/16T(PCI)
30VDC 40mA	Common for all the channels	4 interrupt signals,1 interrupt request	96-pin Half Pitch	○	Attached	○	B-12	PIO-32/32T(PCI)
5VDC 24mA	Common for all the channels	48 interrupt signals,1 interrupt request	96-pin Half Pitch	○	Attached	○	B-12	PIO-48D(PCI)
5VDC 24mA	Common for all the channels	Errors & various factors, 1 interrupt request	96-pin Half Pitch	-	Attached	-	B-13	PIO-32DM(PCI)

Lineup/Basic Knowledge

PCI Bus

Compact PCI Bus

PC Card

USB

Lineup (ISA Bus)

ISA Bus

Output rating	Common	Interrupt	Connector	Software			Page	Name
				ACX-PAC(W32)	API-PAC(W32)	DDE SERVER(W32)		
-	16	4 interrupt signals,1 interrupt request	96-pin Half Pitch	○	○	-	B-14	PI-64L(CPCI)
35VDC 100mA	16	-	96-pin Half Pitch	○	○	○	B-14	PO-64L(CPCI)
35VDC 100mA	16	4 interrupt signals,1 interrupt request	96-pin Half Pitch	○	○	-	B-14	PIO-32/32L(CPCI)

Output rating	Common	Interrupt	Connector	Software			Page	Name
				ACX-PAC(W32)	API-PAC(W32)	DDE SERVER(W32)		
35VDC 100mA	16	16 interrupt signals,1 interrupt request	37-pin D-type	○	Attached	-	B-15	PIO-16/16L(PM)
5VDC 1mA	Common for all the channels	2 interrupt signals,1 interrupt request	37-pin D-type	○	Attached	-	B-15	PIO-24W(PM)
5VDC I _o 6mA, I _i =-2mA	Common for all the channels	32 interrupt signals,1 interrupt request	37-pin D-type	○	Attached	-	B-15	PIO-32D(PM)

Output rating	Common	Interrupt	Connector	Software			Page	Name
				ACX-PAC(W32)	API-PAC(W32)	DDE SERVER(W32)		
-	8	-		○	Attached	-	B-16	DI-16(USB)GY
24VDC 150mA	8	-		○	Attached	-	B-16	DO-16(USB)GY
24VDC 150mA	8	-		○	Attached	-	B-16	DIO-8/8(USB)GY