

## 2 Port Isolated RS-232C Serial Communication Board COM-2P(PCI)H

NEW



Standard COM Driver for  
Windows XP/2000/NT/Me/98/95/Linux included

- FEATURES**
- ★The channels and PCs are insulated among themselves. All the communication lines are surge-protected.
  - ★Can be used as standard COM port on Windows and Linux.
  - ★Up to 16 boards can be added and setting is possible within the range of COM 1 to COM 256.
  - ★FIFO buffer with transmission (128 bytes) and reception (128 bytes) is provided in each channel.
  - High speed communication of up to 921,600bps is supported.

### SPECIFICATIONS

Interface Type	RS-232C (Async.Isolated)
Channels	2ch
Speed	2-921,600bps **
Data type	5-8 bits / 1,1.5,2 stop bit
Parity Check	even, odd, non-parity
Controller	162850 compatible (I/O buffer:128Byte)
Interrupt	one interrupt request signal as INTA
Maximum distance	15m
I/O address	Any 32-byte boundary
Power	+5VDC 600mA (Max.)

Connector	9-pin male D-type, DELC-J9PAF-20L9[JAE] or
PCI bus/ Dimension (mm)	32bit, 33MHz, 5V, 3.3V / 121.69(L)x63.41(H)
Option	
Software	-
Accessories	-
Cables/Connector	RSS-9M/F,RSC-9F RSS-25M/9F RSC-25F/9F,CN5-D9F

\*1. The speed is 15 to 921,600bps in "Standard COM Driver Software COM Setup Disk" and "Driver Library API-PAC(W32)" provided in the attached CD-ROM.

## 4 Port Isolated RS-232C Serial Communication Board COM-4P(PCI)H

NEW



Standard COM Driver for  
Windows XP/2000/NT/Me/98/95/Linux included

- FEATURES**
- ★The channels and PCs are insulated among themselves. All the communication lines are surge-protected.
  - ★Can be used as standard COM port on Windows and Linux.
  - ★Up to 16 boards can be added and setting is possible within the range of COM 1 to COM 256.
  - ★FIFO buffer with transmission (128 bytes) and reception (128 bytes) is provided in each channel.
  - High speed communication of up to 921,600bps is supported.

### SPECIFICATIONS

Interface Type	RS-232C (Async.Isolated)
Channels	4ch
Speed	2-921,600bps **
Data type	5-8 bits / 1,1.5,2 stop bit
Parity Check	even, odd, non-parity
Controller	162850 compatible (I/O buffer:128Byte)
Interrupt	one interrupt request signal as INTA
Maximum distance	15m
I/O address	Any 32-byte boundary
Power	+5VDC 1000mA (Max.)

Connector	37-pin male D-type, DCLC-J37SAF-20L9[JAE] or equivalent
PCI bus/ Dimension (mm)	32bit, 33MHz, 5V, 3.3V / 121.69(L)x63.41(H)
Option	
Software	-
Accessories	-
Cables/Connector	PCE37/9PS,PCE37/25PS,COM-4 CABLE PC1,CN5-D37M

\*1. The speed is 15 to 921,600bps in "Standard COM Driver Software COM Setup Disk" and "Driver Library API-PAC(W32)" provided in the attached CD-ROM.