

# FPS1215AR

## ***10/100M Active PoE Repeater with Splitter power output feature***

◆ **IEEE 802.3at compatible**

◆ **Support 2 Pairs or 4 Pairs PoE**

◆ **Support 12V/1.5Amp Isolated output**



- ★ Easy way for network environment with Remote Power Feeding capability.
- ★ Fully IEEE802.3at-2009 Two Events Classification Support.
- ★ Real-time network monitoring through LED in front panel.
- ★ Active connection for 100M in PoE connection and data connection.

## FPS1215AR Specification :

### ◆ Number of Ports :

\*1 Ports.

### ◆ Data Rate:

\*10/100Mbps.

### ◆ Input Power:

- Using 2 wires or 4 wires PoE connection.
- IEEE802.3af PoE 15W input.
- IEEE802.3at PoE 30W input.
- IEEE802.3at Hi-Power 45W input

### ◆ Output power:

\*12V isolated output.

- 1.5Amp Output Capability
- NOTE: In IEEE802.3af downlink PSE condition need to use 45W Hi-Power PSE input to offer 1.5Amp local power out.

### ◆ LED indicator:

- \*PWR LED : DC power ON.
- \*HiPIN : PoE High Power condition.
- \*PSE ACT: PoE PSE active.

### ◆ Connector:

- \*PoE PD Data In: RJ45.
- \*PoE PSE Data Out: RJ45.

### ◆ Dimension:

\*95 \* 95 \* 38 mm.

### ◆ Environment:

- \*Operating Temperature: -20°C--50°C.
- \*Operating Humidity: 10%--90%RH.
- \*Storage Temperature: -40°C--80°C.
- \*Storage Humidity: 5%--95%RH.

### ◆ Order information:

#### \* **FPS1215AR:**

standard active LAN connection.

## Other Relative products:

- ▲ FPI800: eight port 10/100 PoE power injector.
- ▲ FPI801: eight port 10/100 PoE power injector with DC power input.
- ▲ GPI8000: eight port 10/100/1000 G.Bit PoE power injector.
- ▲ GPI8001: eight port 10/100/1000 G.bit PoE power injector with DC power input.

\*\*\*All names are the trademarks of their respective organization.



## RAYON TECHNOLOGY CO., LTD.

2F, No. 177, Chung\_Shan 2 Rd., Lu\_Chou city, Taipei Hsien, Taiwan.

TEL: 886-2-82858362 FAX: 886-2-82857065

E-Mail: [rayon@msl.hinet.net](mailto:rayon@msl.hinet.net)

WEB: <http://www.computex.com.tw/rayon>

WEB: <http://www.rayontech.com>