

FPS1220A

10/100M Active PoE Splitter

- ◆ IEEE 802.3at compatible
- ◆ Support 2 Pairs or 4 Pairs PoE
- ◆ Support 12V/2Amp Isolated output



- ★ Easy way for network environment with Remote Power Feeding capability.
- ★ Fully IEEE802.3at-2009 Two Events Classification Support.
- ★ Real-time network monitoring through LED in front panel.
- ★ Active connection for 100M in PoE connection and data connection.

FPS1220A Specification :

◆ **Number of Ports :**

*1 Ports.

◆ **Data Rate:**

*10/100Mbps.

◆ **Input Power:**

- Using 2 wires or 4 wires PoE connection.
- IEEE802.3af PoE 15W input.
- IEEE802.3at PoE 30W input.
- IEEE802.3at Hi-Power 45W input

◆ **Output power:**

- *12V isolated output.
- * 2Amp Output Capability

◆ **LED indicator:**

- *PWR LED : DC power ON.
- *HiPIN : PoE High Power condition.
- *PSE ACT: PoE PSE active.

◆ **Connector:**

- *PoE PD Data In: RJ45.
- *Data Out: RJ45.

◆ **Dimension:**

*95 * 95 * 38 mm.

◆ **Environment:**

- *Operating Temperature: -20°C--50°C.
- *Operating Humidity: 10%--90%RH.
- *Storage Temperature: -40°C--80°C.
- *Storage Humidity: 5%--95%RH.

◆ **Order information:**

***FPS1220A:**

standard active LAN connection.

Other Relative products:

- ▲FPI800: eight port 10/100 PoE power injector.
- ▲ FPI801: eight port 10/100 PoE power injector with DC power input.
- ▲ GPI8000: eight port 10/100/1000 G.Bit PoE power injector.
- ▲GPI8001: eight port 10/100/1000 G.bit PoE power injector with DC power input.

***All names are the trademarks of their respective organization.



RAYON TECHNOLOGY CO., LTD.

2F, No. 177, Chung_Shan 2 Rd., Lu_Chou city, Taipei Hsien, Taiwan.

TEL: 886-2-82858362 FAX: 886-2-82857065

E-Mail: rayon@msl.hinet.net

WEB: <http://www.computex.com.tw/rayon>

WEB: <http://www.rayontech.com>