



產品承認書 (APPROVAL SHEET)

公司名稱 (Customer) : _____

商越料號 (P/N) : _____ D2SP64162XH30AAIS

產品名稱 (Part Description) : _____ DDR2-667 1GB 200PIN 寬溫無鉛記憶體模組

製造原廠 (Manufacture) : _____ 商越科技股份有限公司

晶片廠牌 (Dram brand) : _____ (W.T) ProMOS (64MX16)

晶片編號 (Dram P/N:) : _____ V59C1G01168Q(x)J3I

日期 (Date): _____ 2010/09/17

核准 (Approval by)	客戶料號 (Customer P/N:)	承認日期 (Date of Issuance)

商越科技股份有限公司
DATA SPECIALTIES CO.,LTD.

台北市瑞光路 112 巷 1 號 4 樓
TEL:886-2-8642-1883 FAX:886-2-8642-1870

D2SP64162XH30AAIS

Specifications

Density:	1GB	Data Rate:	667 Mbps
Version:	Unbuffered	CAS Latency:	5
Package:	SO-DIMM	Voltage:	1.8V
Pin Count:	200pin	PCB Layers:	6
Speed:	PC2-5300	ECC :	Non ECC
Component Config:	64Meg x 16	Module Ranks :	Dual Rank

Features

- All of Lead-free products are compliant for RoHS
- 200-pin,small outline,dual in-line memory module(SO-DIMM)
- 1.8V ± 0.1V power supply
- Data rate:667Mbps(max)
- 8 Banks
- JEDEC standard 1.8V I/O(SSTL_18-compatible)
- Burst Length: 4,8
- /CAS Latency (CL):3,4,5,6
- Double-data-rate architecture: two data transfers per clock cycle
- Differential clock inputs (CK and /CK)
- Four-bit prefetch architecture
- Auto precharge operation for each burst access
- Auto refresh and self refresh modes
- Differential data strobe(DQS,DQS#) option
- DLL to align DQ and DQS transitions with CK
- Programmable Sequential / Interleave Burst Mode
- Bi-directional Differential Data-Strobe (Single-ended data-strobe is an optional feature)
- Posted CAS# additive latency (AL)
- On Die Termination (ODT)
- 64ms,8192-cycle refresh
- Serial presence detect with EEPROM
- Gold edge contacts
- Operating Temperature Range: -40°C to +85°C (Refresh rate =7.8us)
- -40°C to +95°C (Refresh rate=3.9us)
-
-

D2SP64162XH30AAIS

Description

The D2SP64162XH30AAI Sis 128M words x 64 bits, 2 ranks DDR2 SDRAM Small Outline Dual In-line Memory Module, mounting 8 pieces of 1G bits DDR2 SDRAM sealed in FBGA(μ BGA®) package. Read and write operations are performed at the cross points of the CK and the /CK. This high-speed data transfer is realized by the 4 bits prefetch-pipelined architecture. Data strobe (DQS and /DQS) both for read and write are available for high speed and reliable data bus design. By setting extended mode register, the on-chip Delay Locked Loop(DLL) can be set enable or disable. This module provides high density mounting without utilizing surface mount technology. Decoupling capacitors are mounted beside each FBGA(μ BGA) on the module board.

Speed Grade & Key Parameters

	DDR2-533	DDR2-667	DDR2-800	Unit
CL3	400	400		Mbps
CL4	533	533	533	Mbps
CL5		667	667	Mbps
CL6			800	Mbps
CL-tRCD-tRP	4-4-4	5-5-5	6-6-6	tCK

Speed Bins

	DDR2-533	DDR2-667	DDR2-800	Unit
CL-tRCD-tRP	4-4-4	5-5-5	6-6-6	
Parameter	min	min	min	
CAS Latency	4	5	6	tCK
tRCD	15	15	12.5	ns
tRP	15	15	12.5	ns
tRAS	45	45	45	ns
tRC	60	60	57.5	ns

D2SP64162XH30AAIS

Address Configuration

	256MB	512MB	512MB	1GB	1GB	2GB
Dram Organization	32Mx16	64Mx8	64Mx16	64Mx8	128Mx8	128Mx8
Row address	A0~A12	A0~A13	A0~A12	A0~A13	A0~A13	A0~A13
Column address	A0~A9	A0~A9	A0~A9	A0~A9	A0~A9	A0~A9
Auto Precharge	A10	A10	A10	A10	A10	A10
Bank address	BA0~BA1	BA0~BA1	BA0~BA2	BA0~BA1	BA0~BA2	BA0~BA2
Refresh Method	8K/64ms	8K/64ms	8K/64ms	8K/64ms	8K/64ms	8K/64ms
# of DRAMs	4	8	4	16	8	16

Parameter	Symbol	Rating	Unit	Note
DRAM Component Case Temperature Range	TCASE	-40 to 95	°C	1
Storage Temperature	T _{STG}	-55 to +100	°C	
Storage Humidity	H _{STG}	5 to 95	%	

Absolute Maximum Ratings

Note:

- If the DRAM case temperature is above 85°C, the AUTO-Refresh command interval has to be reduced to tREFI=3.9us.

DC Operating Conditions(SSTL_1.8)

Parameter	Symbol	Min	Typ.	Max	Unit
Supply Voltage	VDD	1.7	1.8	1.9	V
	VDDL	1.7	1.8	1.9	V
	VDDQ	1.7	1.8	1.9	V
Reference voltage	VREF	0.49*VDDQ	0.5*VDDQ	0.51*VDDQ	V
Termination voltage	VTT	VREF - 0.04	VREF	VREF + 0.04	V
Input high voltage	V _{IH}	VREF + 0.15	-	VREF + 0.30	V
EEPROM Supply Voltage	VDDSPD	1.7	-	3.6	V
DC input logic high	V _{IH} (DC)	VREF+0.125	-	VDDQ+0.3	V
DC input low	V _{IL} (DC)	-0.3	-	VREF-0.125	V
AC input logic high	V _{IH} (AC)	VREF+0.250	-	-	V
AC input low	V _{IL} (AC)	-	-	VREF-0.250	V

D2SP64162XH30AAIS

Pin Description

Pin name	Description	Pin name	Description
A0~A13	DDR2 SDRAM address bus	CK0,CK1	Clock input
BA0,BA1	DDR2 SDRAM bank select	/CK0,/CK1	Differential clock input
/RAS	DDR2 SDRAM row address strobe	SCL	Clock input for serial PD
/CAS	DDR2 SDRAM column address strobe	SDA	Data input/output for serial PD
/WE	Write enable	SA0-SA1	Serial address input
S0,S1	DIMM Rank Select Lines	VDD*	DDR2 SDRAM core power supply
CKE0,CKE1	DDR2 SDRAM clock enable lines	VDDQ*	DDR2 SDRAM I/O Driver power supply
ODT0,ODT1	On-die termination control lines	VREF	Input reference supply
DQ0-DQ63	DIMM memory data bus	VSS	Ground
CB0-CB7	DIMM ECC check bits	VDDSPD	Power for serial EEPROM
DQS0-DQS8	DDR2 SDRAM data strobes	NC	No connect
DM(0-8)	DDR2 SDRAM data masks	RESET	Not used on UDIMM
DQS0-DQS8	DDR2 SDRAM differential data strobes	TEST	Unused on memory DIMMs

Pin Configuration

Pin	Front	Pin	Back	Pin	Front	Pin	Back	Pin	Front	Pin	Back	Pin	Front	Pin	Back
1	VREF	2	Vss	51	DQS2	52	DM2	101	A1	102	A0	151	DQ42	152	DQ46
3	Vss	4	DQ4	53	Vss	54	Vss	103	VDD	104	VDD	153	DQ43	154	DQ47
5	DQ0	6	DQ5	55	DQ18	56	DQ22	105	A10/AP	106	BA1	155	Vss	156	Vss
7	DQ1	8	Vss	57	DQ19	58	DQ23	107	BA0	108	RAS	157	DQ48	158	DQ52
9	Vss	10	DM0	59	Vss	60	Vss	109	WE	110	S0	159	DQ49	160	DQ53
11	DQS0	12	Vss	61	DQ24	62	DQ28	111	VDD	112	VDD	161	Vss	162	Vss
13	DQS0	14	DQ6	63	DQ25	64	DQ29	113	CAS	114	ODT0	163	NC,TEST	164	CK1
15	Vss	16	DQ7	65	Vss	66	Vss	115	NC/S1	116	A13	165	Vss	166	CK1
17	DQ2	18	Vss	67	DM3	68	DQS3	117	VDD	118	VDD	167	DQS6	168	Vss
19	DQ3	20	DQ12	69	NC	70	DQS3	119	NC/ODT1	120	NC	169	DQS6	170	DM6
21	Vss	22	DQ13	71	Vss	72	Vss	121	Vss	122	Vss	171	Vss	172	Vss
23	DQ8	24	Vss	73	DQ26	74	DQ30	123	DQ32	124	DQ36	173	DQ50	174	DQ54
25	DQ9	26	DM1	75	DQ27	76	DQ31	125	DQ33	126	DQ37	175	DQ51	176	DQ55
27	Vss	28	Vss	77	Vss	78	Vss	127	Vss	128	Vss	177	Vss	178	Vss
29	DQS1	30	CK0	79	CKE0	80	NC/CKE1	129	DQS4	130	DM4	179	DQ56	180	DQ60
31	DQS1	32	CK0	81	VDD	82	VDD	131	DQS4	132	Vss	181	DQ57	182	DQ61
33	Vss	34	Vss	83	NC	84	NC	133	vss	134	DQ38	183	Vss	184	VSS
35	DQ10	36	DQ14	85	BA2	86	NC	135	DQ34	136	DQ39	185	DM7	186	DQS7
37	DQ11	38	DQ15	87	VDD	88	VDD	137	DQ35	138	Vss	187	Vss	188	DQS7
39	Vss	40	Vss	89	A12	90	A11	139	Vss	140	DQ44	189	DQ58	190	Vss
41	Vss	42	Vss	91	A9	92	A7	141	DQ40	142	DQ45	191	DQ59	192	DQ62
43	DQ16	44	DQ20	93	A8	94	A6	143	DQ41	144	Vss	193	Vss	194	DQ63
45	DQ17	46	DQ21	95	VDD	96	VDD	145	Vss	146	DQS5	195	SDA	196	Vss
47	VSS	48	Vss	97	A5	98	A4	147	DM5	148	DQS5	197	SCL	198	SA0
49	DQS2	50	NC	99	A3	100	A2	149	Vss	150	Vss	199	VDDSPD	200	SA1





D2SP64162XH30AAIS

Input/Output Functional Description

Symbol	Type	Function
<u>CK0-CK2</u> CK0-CK2	Input	CK and /CK are differential clock inputs. All the SDRAM addr/cntl inputs are sampled on the crossing of <u>positive</u> edge of CK and <u>negative</u> edge of CK. Output (read) data is reference to the crossing of CK and CK (Both directions of crossing)
CKE0-CKE1	Input	Activates the SDRAM CK signal when high and deactivates the CK Signal When low. By deactivating the clock, CKE low initiates the Powe Down mode, or the Self-Refresh mode.
/S0-/S1	Input	Enables the associated SDRAM command decoder when low and disables the command decoder when high. When the command decoder is disabled, new command are ignored but previous operations continue. This signal provides for external rank selection on systems with multiple ranks
/RAS,/CAS, /WE	Input	/RAS,/ CAS, and /WE(ALONG WITH CS) define the command being entered.
ODT0-ODT1	Input	When high, termination resistance is enabled for all DQ, /DQ and DM pins, assuming the function is enabled in the Extended Mode Register Set (EMRS).
VREF	Supply	Reference voltage for SSTL 18 Inputs.
VDDQ	Supply	Power supply for the DDR II SDRAM output buffers to provide improved noise immunity. For all current DDR 2 unbuffered DIMM designs, VDDQ shares the same power plane as VDD pins.
BA0-BA1	Input	Selects which SDRAM BANK of four is activated.
A0-A13	Input	During a Bank Activate command cycle, Address input defines the row address(RA0-RA13) During a Read or Write command cycle. Address input defines the column address. In addition to the column address. AP is used to invoke autoprecharge operation at the end of the burst read or write cycle. If AP is high, autoprecharge is selected and BA0, BA1 defines the bank to be precharged. If AP is low, autoprecharge is disbled. During a precharge command cycle, AP is used in conjunction with BA0, BA1 to control which bank(s) to precharge. If AP is high, all banks will be precharged regardless of the state of BA0, BA1. If AP is low, BA0, BA1 are used to define which bank to precharge.
DQ0-DQ63 CB0-CB7	In/Out	Data and Check Bit Input/Output pins.
DM0-DM8	Input	DM is and input mask signal for write data. Input data is masked when DM is sampled High coincident with that input data during a write access. DM is sampled on both edges of DQS. Although DM pins are input only, the DM loading matches the DQ and DQS loading.
VDD, VSS	Supply	Power and ground for DDR2 SDRAM input buffers, and core logic. VDD and VDDQ pins are tied to VDD/VDDQ planes on these modules.
<u>DQS0-DQS8</u> DQS0-DQS8	In/Out	Data strobe for input and output data. For Rawcards using x16 organized DRAMs DQ0-7 connect to the LDQS pin of the DRAMs and DQ8-17 connect to the UDQS pin of the DRAM
SA0-SA2	Input	These signals and tied at the system planar to either VSS or VDD to configure the serial SPD EEPROM address range.
SDA	In/Out	This bi-directional pin is used to transfer data into or out of the SPD EEPROM. A resistor must be connected from the SDA bus line to VDD to act as a pullup on the system board.
SCL	Input	This signal is used to clock data into and out of the SPD EEPROM. A resistor may be connected from the SCL bus time to VDD to act as a pullup on the system board.
VDD SPD	Supply	Power supply for SPD EEPROM. This supply is separate from the VDD/VDDQ power plane. EEPROM supply is operable from 1.7V to 3.6V.

D2SP64162XH30AAIS

FUNCTIONAL BLOCK DIAGRAM



* Clock Wiring	
Clock Input	DDR2 SDRAMs
*CK0/CK0	4 DDR2 SDRAMs
*CK1/CK1	4 DDR2 SDRAMs

* Wire per Clock Loading Table/Wiring Diagrams

- Note :
1. DQ, DM, DQS/DQS resistors : 22 Ohms \pm 5%.
 2. BAx, Ax, RAS, CAS, WE resistors : 3.0 Ohms \pm 5%.

D2SP64162XH30AAIS

Timing Parameters by Speed Grade

Parameter	Symbol	DDR2-800		DDR2-667		Units
		min	max	min	max	
DQ output access time from $\overline{CK}/\overline{CK}$	tAC	-400	400	-450	450	ps
DQS output access time from $\overline{CK}/\overline{CK}$	tDQSCK	-350	350	-400	400	ps
Average clock HIGH pulse width	tCH(avg)	0.48	0.52	0.48	0.52	tCK(avg)
Average clock LOW pulse width	tCL(avg)	0.48	0.52	0.48	0.52	tCK(avg)
CK half pulse period	tHP	Min(tCL(abs), tCH(abs))	x	Min(tCL(abs), tCH(abs))	x	ps
Average clock period	tCK(avg)	2500	8000	3000	8000	ps
DQ and DM input hold time	tDH(base)	125	x	175	x	ps
DQ and DM input setup time	tDS(base)	50	x	100	x	ps
Control & Address input pulse width for each input	tIPW	0.6	x	0.6	x	tCK(avg)
DQ and DM input pulse width for each input	tDIPW	0.35	x	0.35	x	tCK(avg)
Data-out high-impedance time from $\overline{CK}/\overline{CK}$	tHZ	x	tAC(max)	x	tAC(max)	ps
DQS/ \overline{DQS} low-impedance time from $\overline{CK}/\overline{CK}$	tLZ(DQS)	tAC(min)	tAC(max)	tAC(min)	tAC(max)	ps
DQ low-impedance time from $\overline{CK}/\overline{CK}$	tLZ(DQ)	2* tAC(min)	tAC(max)	2* tAC(min)	tAC(max)	ps
DQS-DQ skew for DQS and associated DQ signals	tDQSQ	x	200	x	240	ps
DQ hold skew factor	tQHS	x	300	x	340	ps
DQ/DQS output hold time from DQS	tQH	tHP - tQHS	x	tHP - tQHS	x	ps
DQS latching rising transitions to associated clock edges	tDQSS	-0.25	0.25	-0.25	0.25	tCK(avg)
DQS input HIGH pulse width	tDQSH	0.35	x	0.35	x	tCK(avg)
DQS input LOW pulse width	tDQSL	0.35	x	0.35	x	tCK(avg)
DQS falling edge to CK setup time	tDSS	0.2	x	0.2	x	tCK(avg)
DQS falling edge hold time from CK	tDSH	0.2	x	0.2	x	tCK(avg)
Mode register set command cycle time	tMRD	2	x	2	x	nCK
MRS command to ODT update delay	tMOD	0	12	0	12	ns
Write postamble	tWPST	0.4	0.6	0.4	0.6	tCK(avg)
Write preamble	tWPRE	0.35	x	0.35	x	tCK(avg)
Address and control input hold time	tIH(base)	250	x	275	x	ps
Address and control input setup time	tIS(base)	175	x	200	x	ps
Read preamble	tRPRE	0.9	1.1	0.9	1.1	tCK(avg)
Read postamble	tRPST	0.4	0.6	0.4	0.6	tCK(avg)
Activate to activate command period for 1KB page size products	tRRD	7.5	x	7.5	x	ns
Activate to activate command period for 2KB page size products	tRRD	10	x	10	x	ns

D2SP64162XH30AAIS

Parameter	Symbol	DDR2-800		DDR2-667		Units
		min	max	min	max	
Four Activate Window for 1KB page size products	tFAW	35	x	37.5	x	ns
Four Activate Window for 2KB page size products	tFAW	45	x	50	x	ns
CAS to CAS command delay	tCCD	2	x	2	x	nCK
Write recovery time	tWR	15	x	15	x	ns
Auto precharge write recovery + precharge time	tDAL	WR + tnRP	x	WR + tnRP	x	nCK
Internal write to read command delay	tWTR	7.5	x	7.5	x	ns
Internal read to precharge command delay	tRTP	7.5	x	7.5	x	ns
Exit self refresh to a non-read command	tXSNR	tRFC + 10	x	tRFC + 10	x	ns
Exit self refresh to a read command	tXSRD	200	x	200	x	nCK
Exit precharge power down to any command	tXP	2	x	2	x	nCK
Exit active power down to read command	tXARD	2	x	2	x	nCK
Exit active power down to read command (slow exit, lower power)	tXARDS	8 - AL	x	7 - AL	x	nCK
CKE minimum pulse width (HIGH and LOW pulse width)	tCKE	3	x	3	x	nCK
ODT turn-on delay	tAOND	2	2	2	2	nCK
ODT turn-on	tAON	tAC(min)	tAC(max)+0.7	tAC(min)	tAC(max)+0.7	ns
ODT turn-on (Power-Down mode)	tAONPD	tAC(min)+2	2*tCK(avg) +tAC(max)+1	tAC(min)+2	2*tCK(avg) +tAC(max)+1	ns
ODT turn-off delay	tAOFD	2.5	2.5	2.5	2.5	nCK
ODT turn-off	tAOF	tAC(min)	tAC(max)+0.6	tAC(min)	tAC(max)+0.6	ns
ODT turn-off (Power-Down mode)	tAOFPD	tAC(min)+2	2.5*tCK(avg) +tAC(max)+1	tAC(min)+2	2.5*tCK(avg) +tAC(max)+1	ns
ODT to power down entry latency	tANPD	3	x	3	x	nCK
ODT power down exit latency	tAXPD	8	x	8	x	nCK
OCD drive mode output delay	tOIT	0	12	0	12	ns
Minimum time clocks remains ON after CKE asynchronously drops LOW	tDelay	tIS+tCK(avg) +tIH	x	tIS+tCK(avg) +tIH	x	ns

D2SP64162XH30AAIS

Declaration of Compliance with the RoHS Directive

DATA SPECIALTIES CO.,LTD Hereby declares that the products compliant with the European Union Directive 2002/95/EC for Restriction of the use of certain Hazardous Substances in Electrical and Electronic Equipment(RoHS Directive).

Below list of DSL(DATA SPECIALTIES CO.,LTD.) products are Compliance.

No.	Substance	Max. Conc.
1	Cd (Cadmium)	<100ppm
2	Hg (Mercury)	<1000ppm
3	Pb (Lead)	<1000ppm
4	Cr+6 (Hexavalent Chromium)	<1000ppm
5	PBB (Polybrominated Biphenyl ethers)	<1000ppm
6	PBDE (Polybrominated Diphenyl)	<1000ppm

DATA SPECIALTIES CO., LTD.

Approved: [Quality Engineering Team](#)

Issued Date: [2007-06-20](#)

Doc No: [DS-0706-20](#)

D2SP64162XH30AAIS

Declaration of Compliance with the PFOS Directive

DATA SPECIALTIES CO.,LTD Hereby declares that the products compliant with DIRECTIVE 2006/122/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL regarding exception of the use in photoresist or anti reflective coatings for photolithigraphy(usually semiconductor).

Only some kind of DATA SPECIALTIES CO.,LTD. Use PFOS in photoresist process, but do not contain PFOS in the Product.

DATA SPECIALTIES CO., LTD.

Approved: [Quality Engineering Team](#)

Issued Date: [2008-07-01](#)

Doc No: [DS-0807-01](#)